

Maxol Extendo 5W30

Maxol Extendo 5W/30 is universal motor oil developed using the most recent lubricant technology providing fuel economy as well as a range of other benefits. **Maxol Extendo 5W/30** is built on carefully selected base oils as well as a well balanced choice of advanced additives to obtain the following properties:

- *A lower fuel consumption*
- *Low SAPS content - a fast cold start*
- *A safe lubrication film at high temperatures*
- *Extended oil drain intervals*
- *A very good detergency and dispersion*
- *A very strong protection against wear, corrosion and foaming*

Application

Maxol Extendo **5W/30** is universal oil providing fuel economies and is recommended for use in petrol and diesel engines, with or without turbo-charging, passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension of the lifetime of particulate filters. Due to its special composition it is possible to apply this product extremely for the latest VW 504.00/507.00 requirements.

Performance Level

ACEA A3/B4
VW 504.00/507.00 (pending)

Typicals

Density 15 °C, kg/l	0,850
Viscosity -30 °C, mPa.s	6240
Viscosity 40 °C, mm ² /s	73, 70
Viscosity 100 °C, mm ² /s	11, 60
Viscosity Index	151
Pour Point, °C	-39
Total Base Number, mgKOH/g	6, 1
Sulphate Ash, %	0, 60



MAXOL LUBRICANTS RESERVE THE RIGHT TO CHANGE THIS PRODUCT SPECIFICATION WITHOUT NOTICE